





ABOUT OPKON


Opkon Optik Elektronik A.S. was established in İstanbul in 1993 to produce high-quality position sensors for the machine manufacturing industry and the general automation sector. We offer our customers advanced technology products and solutions with our expert and experienced engineering team.

Opkon's R&D and manufacturing facilities are located in İstanbul at 4000 sqm production area with 128 experienced engineers and technicians. Main products are non-contact magnetostrictive sensors, linear potentiometric transducers, rotary potentiometers, draw wire sensors, linear encoders, rotary encoders and panel type measurement & control devices.


Opkon provides worldwide international sales, service and support with subsidiary offices in Germany and China as well as 88 distribution partners in more than 45 countries. Thus, Opkon can fastly deliver directly from stock.

Opkon pursues its international development by designing, manufacturing, and servicing high-tech products where the quality of its expertise makes all the difference.

Opkon's policy is to meet the expectations of the customers' technical needs with agile solutions and quality products through cost-efficient production with on-time deliveries. In doing so, we attach great importance to occupational health, safety, and environmental protection.



ABOUT OPKON



WHY US ?

- Wide Production Range
- Fast Delivery from Stock
- Custom Design Solutions
- Easy and fast communication
- 30 Years' Experience in R&D, Design and Production
- Worldwide Sales & Service Network
- Engineering Support
- Updated Technology and Innovative Products

ANYTIME YOU NEED US, WE ARE HERE ...

We Are Using All Communication Channels;



+90 553 787 01 30



+90 212 501 48 63

(205-206 Operation), (207-208-210 Sales & Technical Support)



Zoom, Teams, Google Meet




Opkon International, Opkon Optik Elek. Kont. San. ve Tic. A.Ş.



export@opkon.com.tr



www.opkon.com.tr / www.sensormarket.eu / www.danzisensors.com



LONG STROKE RECTILINEAR POSITION TRANSDUCERS (Potentiometric)

Displacement transducers are based on conductive plastic potentiometers for absolute and precise measurement in position control technology.

- 5 kOhm / 10 kOhm
- 30-1950 mm measuring range
- Infinite resolution
- $\pm 0.05\%$ linearity
- ± 0.002 mm repeatability
- 100 million movement mechanical life



ANALOG OUTPUT RECTILINEAR TRANSDUCERS (Potentiometric) AND CONVERTORS

These position sensors are built-in electronic converter circuits with 0-5V, 0-10V, 0-20mA or 4-20mA outputs, to obtain stable position feedback specially for electrical noisy environments.

- 30-1950 mm measuring range
- Infinite resolution
- $\pm 0.05\%$ linearity
- ± 0.002 mm repeatability

Rail and connector type external converters are also in our production range.



SHORT STROKE RECTILINEAR POSITION TRANSDUCERS (Potentiometric)

Absolute measuring potentiometric displacement transducers in a compact design for limited space applications with high repeatability.

- 10-400 mm measuring range
- Infinite Resolution
- $\pm 0.2\%$, 0.5% , 0.05% linearity levels
- ± 0.002 mm repeatability
- 30, 50 and 100 million mechanical movements



ROTARY SENSORS

Rotary resistive sensors are produced with conductive plastic technology. Used for highly sensitive angle and position measurements.

- Measuring angle $345^\circ \pm 2^\circ$
- $\pm 0.5\%$ linearity
- Infinite Resolution

Hall-effect rotary sensors are based on contactless magnetic measurement technology for absolute position measurement.



NON-CONTACT MAGNETOSTRICTIVE SENSORS (Analog Output)

Absolute displacement transducers in a robust design, magnetostrictive (contactless) measuring principle with unlimited mechanical life.

- 100-5000 mm measuring range
- 16 bit resolution
- $\pm 0,005\%$ repeatability
- Single and double output options
- 0-5V, 0-10V, 0-20mA, 4-20mA output
- IP 67 protection



NON-CONTACT, MAGNETOSTRICTIVE SENSORS (Fieldbus Output)

Provides real-time measurements and data transfer with high speed and accuracy based on magnetostrictive measuring technology with digital interfaces.

- 100-5000 mm measuring range
- CANopen, CANbus, Profibus, EtherCAT, Modbus, BISS, SSI output protocols
- 16 bit resolution
- High speed data transfer

IN-CYLINDER POSITION SENSORS (Resistive and Magnetostrictive)

In-cylinder linear position sensors are designed for integration inside a hydraulic or pneumatic cylinder with single or double sensors options for redundancy.

In-Cylinder linear potentiometers;

- 100-1000 mm measuring range
- 5 kOhm / 10 kOhm

Absolute displacement transducer in rod design for installation in cylinders especially for mobile applications; contactless magnetostrictive measuring principle; non-contact position measurement with unlimited mechanical life.

In-Cylinder magnetostrictive sensors;

- 100-3000 mm measuring range
- 0-10 V, 0-20mA, 4-20mA output



NON-CONTACT MAGNETOSTRICTIVE SENSORS FOR LEVEL MEASUREMENT

These magnetostrictive sensors are for level measurement especially in food & beverage industry and also used for other liquid level measurement applications with analog and digital output options.

Analog models;

- 100-5000 mm measuring range
- 0-5V, 0-10V, 0-20mA, 4-20mA analog output
- 16 bit resolution


Digital models;

CANopen, CANbus, PROFIBUS, EtherCAT, Modbus, BiSS, SSI output protocols

LINEAR INCREMENTAL POSITION SENSORS

Linear incremental magnetic position sensors are produced up to 50 meters with high accuracy and resolution.

- 15 - 50.000 mm
- 2.5 / 5 / 10 / 12.5 / 20 / 25 μm resolution
- Product models with optional Push-Pull, TTL Linedriver, HTL Linedriver outputs



PRESS BREAK LINEAR SCALE

MPS model magnetic linear incremental encoders are designed especially for CNC press brake machines.

- Measuring range 150 - 2000 mm
- $\pm 5 \mu\text{m}$ repeatability
- 5 μm resolution
- $\pm 15 \mu\text{m}$ accuracy
- High precision bearing for smooth movement
- Full symetrical
- Adjustable reference
- LED status indicator

ROTARY ENCODERS (OPTICAL / MAGNETIC)

Optic encoders produced with reflective and transmissive technology. Many mechanical and electrical specifications are available.

- 40, 50, 58, 80 or 100 mm body diameter
- 2-5000 ppr high resolution
- Push-Pull, TTL Linedriver or HTL Linedriver and SSI output options



ABSOLUTE, INCREMENTAL MOTOR FEEDBACK ENCODERS (SINE-COSINE / SSI-BISS)

High performance SSI / BISS / SIN-COS output encoders for industrial servo motor applications. Specially used for gearless synchronous elevator motor applications.

- 2048 resolution
- 1 Vpp / 1 ppr, absolute C/D communication signals
- 1 Vpp / 2048 ppr. incremental A/B signals

DRAW WIRE SENSORS

Draw wire Sensors precisely measure the position and have potentiometric and encoder output options with up to 20 meter measurement strokes.

Draw Wire Potentiometer;

- Resistance or analog output
- 0.1%, 0.5%, 0.05% linearity

Draw Wire Encoder;

- Incremental
 - 1000 Pulse (0,2 mm / Pulse)
 - 2000 Pulse (0,1 mm / Pulse)
- Push-Pull, TTL Linedriver, HTL Linedriver



ANALOG TO FIELDBUS CONVERTERS

Rail Type Converters transports the signal from analog output to digital fieldbus output. The Converters are with galvanic isolation between analog and digital output.

- Analog-EtherCAT Converter
- Analog-PROFIBUS Converter
- Analog-Modbus Converter
- Analog-CANopen Converter

PANEL-TYPE MEASUREMENT AND CONTROL DEVICES

- Fast incremental counter
- Indicator for the potentiometric sensors
- Distance and position measurement and control device for potentiometers
- Measurement and control device for voltage/current input potentiometers
- Digital potentiometer
- Loadcell weight measurement controller
- Temperature measurement controller



HOT RUNNER TEMPERATURE CONTROLLERS


High precision accuracy microcontroller, PID function, SSR output hot runner temperature control modules.

- 16 bit high resolution A/D converter
- 1 degree control sensitivity
- PID control
- Thermocouple fault alarm indicator



NOTE

Worldwide Sales Network



Headquarter **R&D , Production**

OPKON Optik Elektronik
Kontrol Sanayi ve Ticaret A.Ş.
Terazidere Mah. 29 Ekim Cad. No:34
Bayrampaşa / İstanbul / TÜRKİYE

Phone : +90 (212) 501 48 63
Fax : +90 (212) 501 48 83
Web : www.opkon.com.tr
E-mail : export@opkon.com.tr

Germany **Subsidiary**

SENSORMARKET GmbH
Graeffstrasse.5,
50823 Köln/GERMANY

Phone : +49 22159495400
Fax : +49 22159495402
Web : www.sensormarket.eu
E-mail : sales@sensormarket.eu

China **Subsidiary**

DANZI Sense Technology
(Shanghai) Co., Ltd.
Room 123 -B, F/1, No. 1000 Ziyue Road,
Minhang District, 200240 Shanghai CHINA

Hotline: 400 8050 889
Phone : 021-64091719
Fax : 021-64091713
Web : www.danzisensors.com.cn
E-mail : marketing@opkonchina.com