

Power Adaptor & Power Supply

TDX-5200700



36W/0.7A 52VDC power adaptor, 5.5 x 2.1mm P1J Type DC connector, operating temperature -10°C to 60°C

GS40A48



40W/1.25A 48VDC power adapter with open wire for Terminal Block, operating temperature -30°C to 60°C

GS60A48



60W/1.25A 48VDC Power Adapter with open wire for Terminal Block, operating temperature -30°C to 60°C

DR-30-24



30W/1.5A 24VDC DIN-Rail Power Supply with Input/Output Terminal Block, operating temperature -10°C to 60°C

MDR-40-48



40W/0.83A 48VDC DIN-Rail Power Supply with Input/Output Terminal Block, operating temperature -20°C to 70°C

EDR-75-48



75W/1.6A 48VDC DIN-Rail Power Supply with Input/Output Terminal Block, operating temperature -20°C to 60°C

DR-120-48



120W/2.5A 48VDC DIN-Rail Power Supply with Input/Output Terminal Block, operating temperature -10°C to 60°C

DRP-240-48



240W/5A 48VDC DIN-Rail Power Supply with Input/Output Terminal Block, operating temperature -10°C to 70°C

DRP-480S-48



480W/10A 48VDC DIN-Rail Power Supply with Input/Output Terminal Block, operating temperature -10°C to 70°C