

METRICU M-IPC-200 B

KAMEROIDEN HUOLTONMONITORI



3.5" näytöllä varustettu IP- ja analogisten kameroiden testeri. CVBS, sekä HD-TVI, HD-CVI, AHD signaalien tuki. Jännitesyötö tö kameroille DC12V 3A, tai DC48V PoE. UTP kaapelitesti, RJ45 liittimen kautta katkennen kaapelin pituuden mittaus TDR testillä. Rannekiinnitys

- » Analogisten kameroiden testaus
- » IP kameroiden testaus, tukee ONVIF, 4K, H.264 ja H.265
- » HD-TVI, HD-CVI ja AHD kameroiden testaus
- » Tuki DC12V 3A, DC48V PoE tehon ulostuloille
- » UTP kaapelitesti, RJ45 kaapelin TDR testi
- » Rannehihna
- » Punainen, kuminen suojaakuori

TEKNISET TIEDOT

Model Number	M-IPC-200B
Signal System	NTSC / PAL (Auto-Selecting)
Display	4 inch touch screen, 800*480 resolution
PTZ Protocol	PTZ control, RS485 control, Baud 600-115200bps, compatible with more than 30 protocols such as PEL-CO-D/P, Samsung, Panasonic etc.
IP camera type	4K, H264, H265, Onvif, Onvif PTZ, ACTi, Dahua IPC-HFW2100P, Hikvision, DS-2CD864-E13, Samsung SNZ-5200, Honeywell HICXC-2300T, etc. Customized protocols are available
Rapid Video	Auto view the video, create testing report
Hikvision test tool	Pressing just one key to activate hikvision camera , Image test, can modify the user name, password and IP parameters
Dahua test tool	Dahua camera test, modify the user name, password and IP parameters
Network test	Trace route, Link monitor, DHCP server, port flashing, Ping test
HD-TVI input	8MP TVI camera test, 3840 x 2160, 15 FPS, image display, zoom, video record and playback, coaxial PTZ control and call camera OSD menu
HD-CVI input	8MP CVI camera test, 3840 x 2160, 12.5/15 FPS, image display, zoom, video record and playback, coaxial PTZ control and call camera OSD menu
AHD input	8MP AHD camera test, 3840 x 2160, 15 FPS, image display, zoom, video record and playback, coaxial PTZ control and call camera OSD menu
Zoom Image	4x zoom, to enlarge image, Screen snapshot, record ,save ,view and record and play back
Network Port	10/100/1000M auto adapt, RJ45
12V/3A power	DC12V 3A power output, supply temporarily power for the camera
PoE power output	48V PoE power output, max power 25.5W
UTP cable test	Test UTP cable connection status and display on the screen. Read the number on the screen
RJ45 cable TDR test	Test cable pair status, length, attenuation, reflectivity, impedance, skew etc. measurement range 180M
Wi-Fi	Built in WIFI, speeds 150M, display wireless camera image
Audio test	1 channel audio signal input
Data monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal
External power supply	DC 12V 1A
Battery	Built-in 7.4V Lithium polymer battery, 2400mAh
Rechargeable	After charging 3-4 hours, normal working time 8 hours
Operation setting	OSD menu, select your desired language: English, Korean, Russian, Italian, French, Polish, Spanish, etc
Auto	1-30 (mins)
Dimension	126mm x 82mm x 32mm (Tester); 198mm x162mm x 75mm (box)
Weight	320g (Tester); 810g (Tester with spare parts, box)