

10.4" MDE Video Monitor


Professional Video TFT LCD Monitor

FEATURES

- Special Video Processor.
- NTSC / PAL Auto Switch.
- VESA Standard Bracket.
- Automatic Color Control and Color Killer.
- PIP Control Function (PC / Video).
- 3D De-interlace Technology.
- 3D Comb Filter Technology.
- Friendly OSD Menu.
- Sharpness Enhancement.
- Black Level Extension.
- Shortly Response Time Between Source Switching.
- With M-Star IC.
- Monitor Identification Setting Function.
- 3-D Video Noise Reduction.
- Aluminum Panel Frame. Metal Case.
- Plastic Panel Frame, Metal Case. (10.4 Option ONLY)



CONNECTORS



SPECIFICATIONS

MODEL	CH-L104AV-1MDEL	CH-L104AV-3MDEL	CH-L104AK-2MDE
Operating System	NTSC / PAL Auto Switch		
LCD Panel	10.4" TFT		
Viewable Area (H/V-mm)	211.2 x 158.4		
Profile Ratio	4:3		
Max. Resolution (H/V)	800 x 600	800 x 600	1024 x 768
Display Color	16.7M		
Brightness (nit)	250 nit (LED B/L)	400 nit (LED B/L)	300 nit
Contrast Ratio	500 :1	700:1	500:1
Response Time (Tr/Tf-ms)	35 ms	30ms	25ms
Viewing Angle (U/D/L/R)	50/60/70/70	60/80/80/80	50/60/70/70
Input Video Signal	2x(Composite Video):1.0Vp-p 75Ω, 1x(S-Video), Y(1.0-Vp-p), C(0.258-V-p-p), 1x(Analog RGB)		
Input Audio Signal	2 x Audio (R/L) 50~100m Vp-p, 1 x Earphone Out		
Input / Output Impedance	75Ω Auto Termination		
Panel Frame	Aluminum / Plastic (Option)		
Controls	Source / Menu / Item / Adjust / Power		
Remote Control	YES		
Video Connector	BNC (in) x 2, BNC (out) x 2, 4P Mini Din (In) x 1, 15Pin D-Sub x 1		
Audio Connector	RCA Jack (R/L)In x 2, 1CH Earphone Out x 1, Audio Speaker x 2 (2W+2W)		
Environment	Operating : (0°C ~ 50°C) / Humidity : 10% ~ 85% (32°F~122°F) Storage : (-10°C ~ 60°C) / Humidity : 10% ~ 85% (14°F~140°F)		
Power Supply	AC 90~260VAC 60HZ/50HZ, Global Switching Power Adapter 12V 3A		
Power Consumption	10W	10W	15W
Net Dimension (W x H x D)	266.2 x 213.3 x 57.4mm (10.48 x 8.39 x 2.25 Inch)		
Net Weight	2.4kg		

INTERFACE

