

# LX Range



LX.1000



LX.3000



LX.3000C Typical Indoor Enclosure

An economy range of general purpose DC Linear Power Supplies for Security Applications

## Features

1. 12 or 24 volt DC switchable by on-board jumper (appropriate transformer required)
2. Variable Pot on-board for precise voltage setting
3. On-board varistor for transience suppression.
4. Battery charging circuit current limited
5. Battery charging leads provided
6. Green LED indicator for AC Input
7. Red LED indicator for DC output
8. PTC or conventional fuse option
9. Available in PCB format, boxed, or chassis mounted
10. Boxed models fitted with tamper micro-switch
11. Weatherproof models to IP.66 available on request
12. Own brand corporate decal available on boxed models (bulk or call off orders only)

**For larger Amperage Power Supplies see the ST and SX ranges.**

**For Monitored Power Supplies see the MT and SX(M) ranges.**

**For 24 Vac Power Supplies see the AT and CT ranges.**

## Models available

|         |         |
|---------|---------|
| LX.1000 | 1 Amp   |
| LX.1500 | 1.5 Amp |
| LX.2000 | 2 Amp   |
| LX.3000 | 3 Amp   |

## Dimensions

|                  |                  |
|------------------|------------------|
| LX.1000 pcb      | 63 X 63 X 35mm   |
| LX.1500 pcb      | 63 X 63 X 35mm   |
| LX.2000 pcb      | 63 X 63 X 35mm   |
| LX.3000 pcb      | 105 X 70 X 50mm  |
| LX. Boxed Models | 210 x 235 x 90mm |

**FOR MORE DETAILED TECHNICAL INFORMATION  
PLEASE SEE INDIVIDUAL PRODUCT DATA S**